Specification Sheet



SOLYX_® Glass Finishes SXWF-WF White Frost



Product Description

SOLYX® SXWF-WF White Frost is a translucent frosted polyester film with a very light texture. It is ideal for obscuring direct visibility while allowing good light transmission.

Specifications

Product CodeSXWF-WFProduct FamilyFrostedFilm TypePolyesterAdhesive TypePressure-SensitiveUsageInterior or ExteriorAvailable Width(s)48", 60"Full Roll Length100 linear feet (30.5m)Thickness2 milShading Coefficient0.82Visible Light Transmission38%UV Transmission24%Solar Heat Reflection18%Solar Energy Absorbed20%		
Film TypePolyesterAdhesive TypePressure-SensitiveUsageInterior or ExteriorAvailable Width(s)48", 60"Full Roll Length100 linear feet (30.5m)Thickness2 milShading Coefficient0.82Visible Light Transmission38%UV Transmission24%Solar Heat Reflection18%	Product Code	SXWF-WF
Adhesive TypePressure-SensitiveUsageInterior or ExteriorAvailable Width(s)48", 60"Full Roll Length100 linear feet (30.5m)Thickness2 milShading Coefficient0.82Visible Light Transmission38%UV Transmission24%Solar Heat Reflection18%	Product Family	Frosted
UsageInterior or ExteriorAvailable Width(s)48", 60"Full Roll Length100 linear feet (30.5m)Thickness2 milShading Coefficient0.82Visible Light Transmission38%UV Transmission24%Solar Heat Reflection18%	Film Type	Polyester
Available Width(s)48", 60"Full Roll Length100 linear feet (30.5m)Thickness2 milShading Coefficient0.82Visible Light Transmission38%UV Transmission24%Solar Heat Reflection18%	Adhesive Type	Pressure-Sensitive
Full Roll Length100 linear feet (30.5m)Thickness2 milShading Coefficient0.82Visible Light Transmission38%UV Transmission24%Solar Heat Reflection18%	Usage	Interior or Exterior
Thickness2 milShading Coefficient0.82Visible Light Transmission38%UV Transmission24%Solar Heat Reflection18%	Available Width(s)	48", 60"
Shading Coefficient0.82Visible Light Transmission38%UV Transmission24%Solar Heat Reflection18%	Full Roll Length	100 linear feet (30.5m)
Visible Light Transmission38%UV Transmission24%Solar Heat Reflection18%	Thickness	2 mil
UV Transmission24%Solar Heat Reflection18%	Shading Coefficient	0.82
Solar Heat Reflection 18%	Visible Light Transmission	38%
	UV Transmission	24%
Solar Energy Absorbed 20%	Solar Heat Reflection	18%
	Solar Energy Absorbed	20%
Glare Reduction 28%	Glare Reduction	28%
Infra-Red Transmission 41%	Infra-Red Transmission	41%
Total Solar Energy Rejected 38%	Total Solar Energy Rejected	38%

Product Construction

Face Film 2 mil Polyester

Adhesive Clear, Pressure-Sensitive

Release Liner Silicone Coated

Product Details

SOLYX® SXWF-WF White Frost is a translucent frosted polyester film with a very light texture. Manufactured with a silicone coated liner which protects the clear, pressure-sensitive adhesive, this film is designed for application to interior glass, single- or double-pane, and exterior facing-glass as well as to exterior glass. It is ideal for privacy, decorative, or architectural applications.

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code[®].

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

Warranty

This **SOLYX®** product will be free from defects in material and manufacture for a period of ten (10) years from the date of installation. Exterior applications have a three (3) year warranty. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC 1-888-657-5224 www.decorativefilm.com

